



GREEN SOLUTIONS GS220 Hi Tac Wall & Sheet Vinyl Adhesive

BENEFITS

- ✓ Installer Friendly
- ✓ Creating A Safer Work Environment
- ✓ Beneficial To Building Occupant
- ✓ Building Green Credits
- ✓ A Good Environmental Choice

FEATURES

- ✓ Green Star Compliant
- ✓ GECA Licensed
- ✓ Solvent Free
- ✓ Very Low VOC Emission
- ✓ Anti-microbial Formulation
- ✓ Very Low Odour
- ✓ Australian Made

RLA POLYMERS GREEN SOLUTIONS PREMIUM COMMERCIAL PRODUCTS are helping you to have a safer work place. During the installation period and for some further time, they will help improve the occupied work space air quality by reducing green house gas, solvent, organic and other volatile emissions.

PRODUCT DESCRIPTION

GS220 Green Solutions Premium Commercial Hi Tac Wall & Sheet Vinyl Adhesive is a synthetic acrylic polymer blend specifically formulated to achieve high initial tack and high bond strength when final cure has taken place.

FOR BONDING

Specifically formulated for bonding wall and sheet vinyls as well as backed and unbacked wall fabrics. The cured film is easily reactivated to help roll out bubbles and other surface imperfections when warmed.

GS220 Green Solutions Premium Commercial Hi Tac Sheet & Wall Vinyl Adhesive should not be used to install vinyl plank flooring. Use **GS200 RLA Polymers Green Solutions Premium Multipurpose Vinyl Adhesive**.

SURFACE PREPARATION

To be in accordance with the Australian/New Zealand Standards AS/AZ2455.1 2007 "Textile Floor Coverings - Installation Practice" and AS1884-1985. All surfaces to be bonded shall be dry, smooth, sound, clean and free of wax, grease and moisture. The minimum substrate temperature before commencing surface preparation and adhesive application is 10°C.



Lic: RLA-2008
www.geca.org.au



The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia
P.O. Box 147, Kilsyth, Victoria 3137 Australia
Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009
E-mail: info@rlapolymers.com.au • Web: www.rlapolymers.com.au



67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand
Telephone: (9) 268 0301
Facsimile: (9) 268 0305

It is recommended that all porous substrates including plaster surfaces should be primed using **GS400 RLA Polymers Green Solutions Premium Commercial Floor & Wall Primer** before the application of the adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian Standards prior to undertaking surface priming or installation of floorcoverings.

SPREAD RATE & APPLICATION

Roller: up to 7 square meters per litre. 1.6mm (V1) trowel up to 5 square meters per litre. Adhesive can be applied by roller or fine "V" notch trowel for wall coverings. For sheet vinyl adhesive should be spread evenly with a 1.6mm deep x 1.6mm wide trowel (V1). The vinyl or fabric should be placed into the wet film of adhesive and completed as per the covering manufacturer's recommendations.

Complete the installation by rolling the wall or floor vinyl covering in both directions with a suitable roller prior to the adhesive setting.

CLEAN UP

Clean tools immediately after use with warm soapy water.

TYPICAL PROPERTIES

Appearance	Creamy
Base	Acrylic
Solids	Approx 78%
Viscosity	Trowellable/Rollable
Tack-up	15-20 minutes at 25°C

CONTAINER SIZE

15 litres.

STORAGE

Recommended to be at temperatures between 10°C and 30°C. Keep in well ventilated areas away from sources of heat and direct sun light.

SHELF LIFE

12 months in unopened containers stored under appropriate conditions.

SAFETY & HANDLING

A Material Safety Data Sheet is available upon request.

Issued: June 2008