



Flexigrout TM

Premixed flexible grouting system

Characteristics:

- Designed for use as a pointing mortar for bricks, stone and tiles.
- Ideal for grouting over membranes and highly flexible adhesives such as Butylbond.
- Flexi-Grout TM is a high solids polymer product, containing various fillers and colour.
- The product uses organic polymers, and contains no dangerous solvent or hydrocarbons.
- Once cured the product will remain permanently flexible and colorfast.
- Expected service, up to 15 years.
- Available in standard colours - Off-white, Sand, Mid Grey, Slate Grey, Black, Terracotta

Properties:

Solids (Polymer)
pH
Specific gravity
Viscosity
Auto Ignition
Chloride Ion Resistance
Acid Resistance

Results:

50% +
10 - 11
1.50
Thick
Nil
Excellent
Excellent

Durability:

- Expected service life of up to 15 years, after which time oxidation may act as a breakdown mechanism. Simply wire brush and re grout or point over existing.

Appearance:

- Uncoloured Creamy Off White
Can be made to any colour (see above under 'characteristics' for standard colours)

Packaging:

- Standard 10 litre pails

Uses:

- Designed for use as a grout or pointing mortar for bricks, stone and tiles. Ideal for restoration work.

Applicable Substrates:

- The product can be applied to concrete, masonry block, cement boards, bricks, stone and all forms of tiles.
- Always ensure substrates are free of contaminants, and relatively dust free.

Application:

- Easiest application method is with a gun and nozzle or commercial icing bag. Can be tooled in.
- Can be applied using a rubber grouting float or squeegee, ensuring that as you go, you remove as much surplus grout from the tile surface as possible.
- On hot days finish as you go to avoid product skinning over.

Compatibility:

- Compatible with all types of cement based substrates, tiles and bricks.

Coverage:

- Coverage is dependent on the thickness of application.
- As an Approximate guide, 1 litre will fill a joint at 10mm wide by 10mm deep and 10 metres long.

NOTE: All statements and technical information contained herein are based on tests we believe to be reliable and the accuracy thereof is not guaranteed. The information contained in our literature or given by our employees, agents or distributors about our products and their uses are based upon extensive experience of the manufacturer and is given in good faith in order to assist you. Users assume all risk and liability resulting from the use of our products and must confirm the suitability thereof by their own onsite tests. Conditions of sale contain a limited warranty against manufacturing defects. It is the responsibility of the user to obtain the most recent technical data and instructions for use of any RLA Polymers PTY LTD products. The manufacturer insist that all workmanship must be carried out in accordance with AS3958 part 1 1991



Drying Time:

- Lower temperatures or on days of very high humidity or rain will extend drying times.
- The product should not be applied in temperatures less than 10°C, or temperatures above 40°C
- Skin Formed 30 minutes at 20°C
- 100% 5 – 7 days (dependant on conditions)
- If there is high humidity, rain is imminent, or winter conditions prevail, a cup full of cement mixed with water into a thick paste and then added to 10 litres of Flexi-Grout will enhance curing.
- This catalyses the alkaline curing mechanism.
- Use white or grey cement depending on Flexi-Grout colour.

DO NOT GROUT TILES WITH WATER ENTRAPPED UNDER THE TILES

WARNING: FRESHLY LAID PRODUCT MAY WASH OUT IF EXPOSED TO RAIN OR DEW WHILE CURING. WATER UNDER TILES WILL NOT ALLOW PRODUCT TO CURE.

Washing up:

- Clean up tools and hands with fresh, clean water. Clean immediately after use. Cured product may prove more difficult to clean off later.

Storage:

- Store in a cool dry area, the same as for paints. Do not store in direct sunlight.
- The product is classed as non-dangerous and non-flammable. Protect from frost.

Health and Safety

- Swallowed May cause abdominal discomfort, nausea or diarrhoea. Give copious amounts of water to drink. Consult a doctor.
- Eye Contact Use safety glasses. Eyes will become irritated. Irrigate with water. Consult a doctor if irritation persists.
- Skin Contact Avoid prolonged skin contact. May cause rashes on sensitive skins. Wash from skin with warm, soapy water.
- Inhalation When using spray application, wear a mask, especially in poorly ventilated areas.

In all cases consult medical advice if unsure.

NOTE: All statements and technical information contained herein are based on tests we believe to be reliable and the accuracy thereof is not guaranteed. The information contained in our literature or given by our employees, agents or distributors about our products and their uses are based upon extensive experience of the manufacturer and is given in good faith in order to assist you. Users assume all risk and liability resulting from the use of our products and must confirm the suitability thereof by their own onsite tests. Conditions of sale contain a limited warranty against manufacturing defects. It is the responsibility of the user to obtain the most recent technical data and instructions for use of any RLA Polymers PTY LTD products. The manufacturer insist that all workmanship must be carried out in accordance with AS3958 part 1 1991