



S O L U T I O N S F O R I N D U S T R Y

## Polyurethane Adhesive 1017

## Specialised Adhesives

**RL1017 is a one part Solvent Free Polyurethane Adhesive for the installation of both Block and Mosaic Parquetry, Strip or laminated Flooring and Sheet type timber systems to most common building substrates. The adhesive when cured is flexible and water resistant. RL1017 required atmospheric moisture to cure fully and therefore totally confined areas should be avoided.**

### Surface Preparation

To be in accordance with any relevant Australian Standard. All surfaces to be bonded shall be dry, smooth, south and clean. Subfloors must also be free of wax, grease & hydrostatic pressure.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C.

All concrete substrate floors should be tested for moisture content, according to Australian Standard 1984-1985 appendix 3 prior to installation of floorcovering.

### Application

Apply adhesive to substrate with a 3mm "V" notched spreader for wood block and mosaic parquetry. Slightly smaller notches depending on spacing may be used on certain materials being fixed is achieved.

All materials should be placed into wet freshly spread adhesive.

Initial setup will be approximately 5-7 hours depending on temperature. Do not allow heavy traffic for 24 hours. Roll within 1 hour of laying.

### Clean Up

Clean tools immediately after use with suitable Solvent Cleaner. When cured it is difficult to remove by chemical means, mechanical means are necessary.

### Technical Data

#### Appearance

Beige

#### Base

Polyurethane

#### Solids

Almost 100%

#### Viscosity

Trowellable

#### Shelf Life

Up to 1 year in sealed container at 20°C

#### Freezability

Do not freeze.

#### Packaging

10 litre pails  
600 ml sausages

#### Trowel Size

3.2 mm "V" notched  
Coverage up to 1.7m<sup>2</sup> per litre

#### Packaging & Storage

It requires atmospheric moisture to cure and consequently is sensitive to moisture whilst in storage. Keep containers tightly sealed and foil bag sealed in the partly used pail.

Store in cool dry place, avoid direct sunlight.

#### Safety & Handling

Avoid contact with skin and eyes, avoid breathing vapours. A Materials Safety Data Sheet is available upon request.

### RLA POLYMERS PTY LTD

ACN 004 709 915

#### Australia

215 Colchester Road, Kilsyth  
Victoria 3137, Australia

Telephone (03) 9728 1644

Facsimile (03) 9728 6009

Email: [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au)

#### Queensland

Telephone (07) 3807 4022

Facsimile (07) 3807 4755

#### New South Wales

Telephone (02) 9609 4755

Facsimile (02) 9604 3199

#### New Zealand

67 Dalgety Drive, Manukau City  
Auckland, New Zealand

Telephone (9) 268 0301

Facsimile (9) 268 0305

#### Malaysia

No 5, Lebuhraya Petai, Pandamaran  
42000 Port Klang, Selangor D.E.

Telephone 03-31661039

Facsimile 03-31661037



A British Vita Group Company



*All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.*