

6135 CONSTRUCTION ADHESIVE

PRODUCT DESCRIPTION

Roberts 6135 Construction Adhesive is a versatile mastic, developed for bonding most common materials used in the construction industry. These include timber, masonry, brick, galvanised iron, steel and polystyrene foam.

Roberts 6135 is a high solids product that forms a very tough, flexible glue base. It is primarily used in sheet flooring and wall panelling.

SURFACE PREPARATION

Surfaces to be bonded should be clean, dry and free from dust and oil.

TYPICAL PROPERTIES

<i>Appearance</i>	<i>Light brown</i>
<i>Base</i>	<i>Synthetic Elastomeric Polymer</i>
<i>Flash Point</i>	<i>Less than 0°C</i>
<i>Viscosity</i>	<i>Heavy mastic</i>
<i>Shelf Life</i>	<i>Minimum 12 months in sealed containers at 20°C</i>

DRYING TIME

Initial bond in 1 to 30 minutes. Handling strength in 30 minutes to 24 hours. All drying times are dependent on porosity of materials and ambient temperature.

CLEAN UP

Clean up excess adhesive and tools with Mineral Turps.

APPLICATION

Roberts 6135 Construction Adhesive should be applied to one surface and the other surface pressed onto the adhesive and held securely in place. For fast setting bonds, separate surfaces for 2 to 5 minutes – reposition and press in place.

Temporary fastening is not normally required when fixing lightweight materials such as polystyrene foam. Manufacturer's nailing instruction must be followed when fixing sheet flooring.

SAFETY DIRECTIONS

Storage

Store in a well ventilated area way from oxidising agents and avoid direct sunlight.

Warning

Flammable. Always provide adequate ventilation. Keep away from heat, sparks, naked flames, etc.

Disposal

Please dispose of empty containers and residue in accordance with your local waste management regulations.

SAFETY & HANDLING

A Material Safety Data Sheet is available on request.

Issued: August 2007

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

adhesives
tapes
melting
powders
hot melt
tapes